

**Call 1-800-323-5158 for more information or to order**

**Email: [help@on-hand.com](mailto:help@on-hand.com) You may print out this page**

NOT FOR PRODUCT SPECIFICATIONS. THE DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

## **Material Safety Data Sheet Titan 7565**

### **1- Chemical Product and Company Identification:**

Product Name: **Titan 7565** Product Type: Anaerobic Sealant

### **2- Composition/Information on Ingredients:**

Hazardous Component CAS Number %

Dimethacrylate Ester 25852-47-5 65-75

Bisphenol A Fumurate Resin 39382-25-7 20-30

Saccharin 81-07-2 1-3

Polyethylene 9002-88-4 1-3

Amorphous Silica 112945-52-5 0.1-1.0

Cumene Hydroperoxide\* 80-15-9 1-3

Organic Acid Trade Secret 0.1-1.0

Dyes Trade Secret 0.03-0.10

\*SARA Section 313 Toxic Chemical

Ingredients which have exposure limits

Exposure Limits (TWA) ACGIH (TLV) OSHA (PEL) OTHER

Amorphous Silica 10mg/m<sup>3</sup> TWA 6mg/m<sup>3</sup> TWA 3mg/m<sup>3</sup> TWA

resp. dust

Exposure Limits (STEL)

### **3- Hazards Identification:**

Toxicity: Mild Eye Irritant

Primary routes of Entry: Eyes, skin

Signs of exposure: May cause dermatitis on prolonged contact in sensitive individuals.

Existing Conditions

Aggravated by Overexposure: None Known

### **4- First Aid Measures:**

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Does not apply.

Skin contact: Wash affected area with soap and water.

Eye contact: Flush with warm water. Seek competent medical attention.

### **5- Fire Fighting Measures:**

Flash Point: 150-200F, Tag Closed Cup

Extinguishing Media: Foam, Dry Chemical or Carbon Dioxide

Unusual Fire or Explosion Hazards: None.

Special Fire Fighting Procedures: None.

**7565 Page 1 of 3** Material Safety Data Sheet Titan 7565

Hazardous Products formed by

Fire or Thermal Decomposition : Irritating Organic Vapors

### **6-Accidental Release Measures**

Steps to be taken in case of spill or leak: Soak up with inert absorbent. Store in a partly filled, closed container

Until disposal.

### **7- Handling and Storage:**

Safe storage: Store below 100°F.

Handling: Avoid contact with skin and eyes.

### **8- Protective Equipment:**

Ventilation: Does not apply.

Respiratory protection: Not applicable.

Skin: Rubber, Polyethylene, or neoprene gloves.

Eye protection: Safety glasses or goggles with side shields.

9- Physical and Chemical Properties:

Appearance: White Paste

Odor: Mild

Boiling Point: Greater than 300F

Vapor Pressure: Less than 5mmHg @20C

Vapor Density: Approximately 3 (Air =1)

Evaporation rate: Not applicable

Specific Gravity: 1.04

Solubility in water: Negligible.

10- Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility: None

11- Toxicological Information

See Section 3

12- Ecological Information

No Data

7565 Page 2 of 3 Material Safety Data Sheet Titan 7565 7565 Page 3 of 3

13- Disposal Considerations:

Disposal procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations. Not a RCRA hazardous waste.

14- Transportation Information:

Domestic Ground Transport:

Proper shipping name: Unrestricted (not more than 450 liters)

Combustible liquid, n.o.s. (more than 450 liters)

Hazard class or division: Unrestricted (Not more than 450 liters)

Combustible liquid (more than 450 liters)

Identification number: None (Not more than 450 liters)

NA 1993 (More than 450 liters)

Marine pollutant: No

15- Regulatory Information

CA Proposition 65: This product contains saccharin. Proper usage necessitates no Proposition 65 warning

16- Other Information

Hazard NFPA Hazard Code® HMIS Hazard Code®

Health 1 1

Fire 1 1

Reactivity 1 1

Specific Hazard None Personal protection: See Section 8

NFPA is a registered trademark of the National Fire Protection Association

HMIS is a registered trademark of the National Paint and Coatings Association

Prepared by: Kimberly McCall

Company: Cyberbond LLC

Revision Date: 5/05/2003

.



